PRODUCT INFORMATION SHEET

PRODUCT AND SAFETY REGULATIONS

Issued: 18.12.2000

Husqvarna ECO Bevel Gear Lubricant Page 2 (4)

6. IN CASE OF SPILLAGE/ACCIDENTAL DISCHARGE

General: Prevent major discharges in water and drainage systems.

Clean up with appropriate equipment.

Spills cause slipperiness.

7. HANDLING AND STORAGE

Handling: No particular hazards. **Storage:** No particular hazards.

8. RESTRICTION TO EXPOSURE/PERSONAL SAFETY MEASURES

General: No particular technical measures are required.

Observe the usual precautionary measures when dealing with lubricants.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical status: Green grease with mild smell.

Boiling point: >250°C Flash point: >150°C Auto-ignition point: >300°C

Explosive mixture in air: Not applicable

Melting point: 170°C

Density at 20°C:

Solubility in water:

Solubility in org. solvent:

Temperature range:

930 kg/m³

None

Partial

-50 to 120°C

NLGI: 0

Penetration: 355-385
Thickener: Li/Ca
Base oil: Ester

Base oil viscosity at 40°C 50 mm /s
Drip point: 170°C

Corrosion protection, SKF Emcor: 0-0 DIN 51802 Timken OK load, lbs: 45 D-2509